



Steel Pipe And Tubes

Manufacturer **SeAH Changwon Integrated Special Steel Corporation**

Address 147, Jeokhyeon-ro, Seongsan-gu, Changwon-si, Gyeongnam, 51708, South Korea

Type Pipes And Tubes

This approval is subject to compliance with the Rules for the Manufacture, Testing and Certification of Materials. The full details of the processes and grades to which this approval applies are given on subsequent pages of this certificate.

This certificate is issued to the named manufacturer, and is valid until the expiry date specified. Lloyd's Register is to be notified of any change that may affect the validity of this certificate, and reserves the right to cancel or withdraw this certificate.



71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Peter Amin

NDE Team - Senior Specialist to Lloyd's Register EMEA
A member of the Lloyd's Register group

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.



Steel Pipe And Tubes

pipes and tubes	Seamless	Grades	Maximum Diameter	Units
-	-	Carbon	150.00	mm
-	-	Carbon-manganese	150.00	mm
-	-	austenitic stainless	273.00	mm
-	-	duplex stainless	114.30	mm

Additional Remarks

- Approval includes C, C-Mn seamless pipes and tubes with maximum diameter 150mm, wall thickness 22.00mm;
- Approval includes austenitic stainless steel seamless pipes and tubes with maximum diameter 273mm, wall thickness 23.02mm;
- Approval includes duplex stainless (including S32760 super duplex stainless) seamless steel pipes and tubes with maximum diameter 114.30mm, wall thickness 11.07mm, in hot and cold finished process; lowest operating design temperature specified is - 50 °C (minus 50 Degree C)



71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.